


## Summary

The VMAX<sup>®</sup> IP G4<sup>™</sup> is an NDAA and TAA compliant, easy to use embedded PoE network video recorder (NVR) that allows you to go from power up to monitoring in minutes! Available with 4 Power over Ethernet (PoE) ports and expandable to 9 cameras, the NVRs can record and manage single-sensor IP cameras up to 4K resolution and supports up to 16TB internal storage (HDD not included).

## Features

- Complete installation, setup and camera configuration in minutes!
- CCIP<sup>™</sup> system encryption via TLS protects your surveillance system from out of network attacks
- Record and manage single-sensor IP cameras at real-time 30fps up to 4K
- Local power for up to 4 IP cameras via resident PoE switch
- DW Witness<sup>™</sup> turns a smartphone or tablet into a surveillance camera
- PathFinder<sup>™</sup> easy end-to-end remote connection with NAT Traversal (STUN/TURN) support
- Automatic device discovery
- Compatible with ONVIF cameras
- 0-16TB storage options
- Transfer real-time data using Real Time Streaming Protocol (RTSP)
- Snapshot Notify<sup>™</sup>: Interval camera image verification sent to an email
- Remote management with C3<sup>™</sup> CMS for Windows<sup>®</sup> and Mac<sup>®</sup>
- Event camera group recording
- System analysis with real-time system, PoE and network status monitoring
- Event notifications via email, text and push notifications
- Mobile Application for iOS<sup>®</sup> and Android<sup>®</sup> devices
- Dual-stream recording
- Easy drag and drop camera management
- Instant backup during playback
- True HD and VGA simultaneous output support
- Compatible with DW<sup>®</sup> Spot<sup>™</sup> Monitoring module for Public View Monitors
- 4 sensor inputs, 1 relay output
- Advanced H.265/H.264 Linux embedded NVR
- NVR calculation and auto-recording configuration
- Screen saver to protect monitor screen
- Import/export configuration between multiple NVRs
- Auto or manual firmware upgrade available
- NDAA/TAA compliant

## Dimensions Unit: Inch (mm)



## Specifications

VIDEO	
Operating system	Embedded Linux <sup>®</sup>
System	Channel
	No. of PoE
	Max supported resolution
	Communication protocol
Display	PoE type
	Speed
Video out	Screen mode
	Monitor
System operation	Resolution
	USB mouse, PTZ control by keyboard (optional)
PERFORMANCE	
Recording speed	Up to 270fps up to 4K (2160p) resolution
Max. throughput	40 Mbps
Recording streaming	Dual-stream
Recording modes	Continuous, scheduled, sensor and motion detection recording
	Pre- and post-alarm recording, emergency recording, quick backup
Playback and search	Speed
	Channel and resolution
	Function
Audio input / output	1Ch input (disabled)/1Ch output
Alarm input / relay output	4Ch inputs / 1Ch output
PTZ control	RS-485, ONVIF
Storage	HDD interface
	HDD internal storage
	HDD healthcheck
Transaction verification	Text-in Based (USB to Serial support, TCP/IP Network), Display POS Data on Live & Playback
NETWORK	
LAN	1,000Mbps Ethernet (RJ45)
Protocols	IPv4, TCP/IP, DHCP, HTTP, RTSP, STMP, FTP, Zero Configuration, NTP, DDNS
Access	Web viewer
	Video streaming functions
	Monitoring software
Network functions	Live monitoring, remote playback and file backup
Remote system control	Remote system reboot, system management, notifications and remote PTZ control
Remote Time sync	Time synchronization to an NTP server (pool.ntp.org)
Remote system notifications	Notifications for system health, events and alarms
System recovery after power failure	Auto-reboot and journaling file system
Other function	Firmware upgrade
	Back-up
	Special features
	Mobile client
	Health check
GENERAL	
Operating temperature and humidity	32-113 °F (0-45 °C) / 10-90% RH
Certification	CE, FCC, KCC, NDAA, TAA
System	Power requirement
	Power consumption
PoE	Max power per port
	Total PoE power budget
Dimension (W x D x H)	11.81" x 9.8" x 1.77" (300 x 249 x 45 mm)
Warranty	3 year limited



Innovative Electronic Solutions  
www.ness.com.au



NSW Ph 02 8825 9222  
sales@ness.com.au

VIC Ph 03 9875 6400  
nessmelb@ness.com.au

QLD Ph 07 3399 4910  
nessbris@ness.com.au

WA Ph 08 9328 2511  
nessper@ness.com.au

SA Ph 08 8152 0000  
adelaide@ness.com.au