

DS-PDWL-E-WB
Wireless Water Leak Detector

114-268

- Water-proof design for multiple use applications
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Frequency hopping against jamming for reliable transmission



Specifications

	Model	DS-PDWL-E-WB
Feature	Digital Processing	Support
	Tamper Protection	Front, Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
Interface	LED Indicator	Blue (Alarm)
Transmission	Transmission Technology	Tri-X Wireless
	Transmission Method	Two - Way RF Wireless
	Transmission Frequency	433 MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1 Km
	Frequency Hopping	Support
	Enrolling Method	Power up, Remote ID, QR Code
Electrical Characteristics	Power Supply	Battery Powered
	Battery Type	CR2450 x 1
	Typical Voltage	3 V
	Standard Battery Life	3 Years
General	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	IP Rate	IP66
	Dimension(WxHxD)	62.4 mm × 62.4 mm × 14.6 mm
	Weight	85.5 g
	Mounting Method	Wall, Surface
	Application Scenario	Indoor

ORDERING INFORMATION

114-268

Hikvision AX PRO Series Wireless Water Leak Detector



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au