

**DS-D5027UC
Monitor**

114-663



- Designed for video security, high reliability and stability;
- 27" Fashion appearance, very narrow frame;
- 4K resolution is 4 times 1080P can own broader view and more abundant details;
- VESA standard;
- Wide view angle: Horizontal 178°, Vertical 178°;
- High reliability and stability, 24/7 operation;
- Build-in speaker;

▪ Specification

	Model	DS-D5027UC
Display	Viewing Angle	Horizontal 178°, vertical 178°
	Screen Size	27 inch
	Active Display Area	596.736 (H) mm × 335.664 (V) mm
	Backlight	LED Backlight
	Resolution	3840 × 2160@60 Hz
	Brightness	350 cd/m ²
	Contrast Ratio	1000:1
	Response Time	14 ms
	Color Gamut	8 Bit + FRC (1.07 G)
Power	Power Supply	110 to 240 VAC, 50/60 Hz
	Power Consumption	≤ 56 W
	Standby Consumption	≤ 0.5 W
Working Environment	Working Temperature	0 °C to 40 °C
	Working Humidity	10%--85%
	Storage Temperature	-20 °C to 60 °C
	Storage Humidity	10%--80%
General	Casing Material	Black
	VESA	100 mm × 100 mm, 4-M4 × 10 mm
	Material Type	Plastic
	Package Dimension (W × H × D)	690 mm × 140 mm × 480 mm (27.17" × 5.51" × 18.90")
	Net Weight	5.07 kg (11.2 lb.)
	Gross Weight	6.55 Kg (14.4 lb.)
	Dimension (W × H × D)	614.19 mm × 400.5 mm × 249.61 mm (24.18" × 15.77" × 9.83")
Interface	Data Transmission Interface	HDMI input × 1 DP input × 1 AUDIO output × 1
Internal Function	loudspeaker	2 × 2 W

- Accessory
- Optional

DS-DM1940W
Wall-mounted Bracket



ORDERING INFORMATION

114-663 Hikvision DS-D5027UC 27" 4K Monitor



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au