

DS-KIS212 Four-Wire HD Video Intercom Kit

104-102C









- HD TVI video quality
- Plug & play
- One-press to call
- One-press to unlock the door
- Max 2 door stations and 3 indoor stations in one system



Specification

Door station	
Supplement light	IR light, up to 3 m
Resolution	Stream resolution: 1280 * 720@60fps
FOV	Horizontal: 130°, Vertical: 70°
Door station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Door station	
Lock control	1 relay, max 30V 1 A
Debugging port	1
Four-wire	1 four-wire interface
Door station	
Button	1 physical button(s)
Indicator	1
Power supply	12 VDC
Power consumption	Max. 4W
Working temperature	-30° C to + 60° C
Working humidity	10% to 90%
Dimensions	136mm x 51mm x 20mm
Application environment	Indoor
Installation	Surface mounting
Protective level	/
Material	Plastic
Indoor station	
Operation method	Physical button
Туре	7-inch colorful TFT
Resolution	1024 x 600
Indoor station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Indoor station	
Linked indoor extensions	
capacity	2
Linked doorphone capacity	2
Linked analog camera	1
Indoor station	
Power supply input	12V DC
Debugging port	1
Four-Wire interface	4, 2 for indoor extentions, 2 for doorphones
DIP switch	1 Bit
BNC	1
Indoor station	
Button	4 physical button



Power supply	12 VDC
Power consumption	≤5 W
Working temperature	-10° C to + 55° C (14° F to 131° F)
Working humidity	10% to 90%
Dimensions (W × H × D)	178mm x 132mm x 19mm
Installation	Surface mounting
Application environment	Indoor
Protective level	/


Available Model


DS-KIS212

Dimension











Unit:mm [inch]









Unit:mm [inch]









