

DS-KIS212 Four-Wire HD Video Intercom Kit

104-102D



- HD TVI video quality
- Plug & play
- One-press to call
- One-press to unlock the door
- Max 2 door stations and 3 indoor stations in one system

▪ Specification


Door station	
Supplement light	IR light, up to 3 m
Resolution	Stream resolution: 1280 * 720@60fps
FOV	Horizontal: 130°, Vertical: 70°
Door station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Door station	
Lock control	1 relay, max 30V 1 A
Debugging port	1
Four-wire	1 four-wire interface
Door station	
Button	1 physical button(s)
Indicator	/
Power supply	12 VDC
Power consumption	Max. 4W
Working temperature	-30° C to + 60° C
Working humidity	10% to 90%
Dimensions	136mm x 51mm x 20mm
Application environment	Indoor
Installation	Surface mounting
Protective level	/
Material	Plastic
Indoor station	
Operation method	Physical button
Type	7-inch colorful TFT
Resolution	1024 x 600
Indoor station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Indoor station	
Linked indoor extensions capacity	2
Linked doorphone capacity	2
Linked analog camera	1
Indoor station	
Power supply input	12V DC
Debugging port	1
Four-Wire interface	4, 2 for indoor extensions, 2 for doorphones
DIP switch	1 Bit
BNC	1
Indoor station	
Button	4 physical button

Power supply	12 VDC
Power consumption	≤5 W
Working temperature	-10° C to + 55° C (14° F to 131° F)
Working humidity	10% to 90%
Dimensions (W × H × D)	178mm x 132mm x 19mm
Installation	Surface mounting
Application environment	Indoor
Protective level	/


▪ **Available Model**

DS-KIS212

▪ **Dimension**



Unit:mm [inch]



Unit:mm [inch]



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au