

DS-K1104 Pro 1104 Series Metal Vandal-proof Card Reader

114-122
114-123



- M1 card reader
- PC+zinc-alloy material shell
- Built-in audible beeper
- RS-485 and Wiegand interface
- IK10

▪ Specification

Authentication	
Card reading frequency	13.56MHz
General	
Power supply	12 VDC, ≤ 500 mA
Power consumption	≤ 2 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	10% to 90% (no condensing)
Dimensions	118 mm × 76 mm × 23 mm (4.65" × 2.99" × 0.91")
Installation	Applied for 86 & 120 Gang Box
Weight	≤ 0.52 kg (1.1 lb)
Keypad	DS-K1104M: No keypad DS-K1104MK: Keypad with 12 keys (0 to 9, *, #)
Buzzer	Support
Function	
ID settings	via DIP Switch

▪ Available Model

DS-K1104

▪ Accessory

▪ Optional

DS-K7M102-M
M1 Card



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au