

DS-PK1-LT-WB

114-251-LCD



- 433MHz two-way wireless communication
- LCD screen and LED to indicate system status
- System configuration through LCD screen
- Multiple operations like stay/away arm, disarm, silent alarm, output control
- One-Push fire alarm, panic alarm, and medical alarm
- Full touch key design with LED backlight
- Fully remote configurable through App

▪ Specification

Hardware features	
Tag reader built in	Supported
Serial port	3
Tamper-Proof	Supported, front and rear
Buzzer	Supported
Power switch	Power on/off
Electrical characteristics	
Battery type	Four CR123 batteries
Operation humidity	10% to 90%
Operation temperature	-10 °C to +55 °C
Battery life span	Up to 2 years (standby time)
Power consumption	Quiescent current: 80uA Max current: 300mA Voltage: 3v
Wireless transmission	
RF frequency	433 MHz
RF modulation	2GFSK
RF distance	800m (open area)
Wireless technology	Tri-X Wireless Technology
Display	
Numeric key	Number key: 0-9 Function key: *, #, Query, Away arm, Stay arm, Disarm, Output, Project, Right, Left)
LED Indicator	Fault(orange), Enrollment/Signal (red/green), Arm(blue), Disarm(green), Alarm (red)
General	
Installation method	Wall mounting
Dimension(WxHxD)	174.63*109.62*25.25mm
Weight	With batteries:348g Without batteries: 282g
Color	White

▪ Available Model

DS-PK1-LT-WB



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au