

DS-KIS708EY
2-wire HD DIY villa kit

114-563



- Great image quality of 2MP resolution
- One-press to call, remote unlocking with App control
- Real plug&play
- IP65 water resistant and IK08 vandal resistant entry panel
- 7-inch touch screen indoor monitor, user friendly interface
- Support PIN code to open the door

▪ Specification

Door station	
Processor	Embedded Processor
ROM	4 GB
RAM	256 MB
Operation system	Embedded Linux operation system
Door station	
Screen size	NA
Resolution	NA
Type	NA
Operation method	NA
Door station	
Supplement light	Supplement light Low illumination, IR supplement lights
Resolution	2MP
Lens	1
Wide dynamic range (WDR)	Support
FOV	Horizontal: 135°, Vertical: 85°
Video compression standard	H.264
Door station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Volume adjustment	Adjustable
Audio compression standard	G.711 U, G.726
Audio compression bitrate	64 Kps
Audio quality	Noise suppression and echo cancellation
Door station	
Linked indoor station capacity	Max.400
Sub door station capacity	16
Door station	
Wireless network	10/100 Mbps self-adaptive through 2-wire interface
Wi-Fi	Only AP mode for configuration
Door station	
RS-485	1
Lock control	2 (1 relay, max to 30 VDC, 2 A ; 1 DC pulse, 20V 4A impulsive, 300 mA holding current, 30 ohm max)
Exit button	1
Door contact input	1
Alarm input	2 (supports Exit button or Door contact input)
Power supply input	12VDC input
TAMPER	1
Debugging port	1
Two-Wire	1
DIP Switch	6 decimal DIP switch
Door station	
Button	12


Indicator	4 LED lights(Opening door、 Calling、 Intercom、 In use)
Power supply	48V, Powered by Indoor Station DS-KH7300EY-WTPE2 or 12VDC
Power consumption	≤ 6 W
Working temperature	-40° C to 60° C (-22° F to 140° F)
Working humidity	10% to 90%
Application environment	Outdoor
Dimension (W × H × D)	165mm × 95 mm × 25 mm(6.5" × 3.7" × 0.98")
Installation	Surface mounting
Protective level	IP65 IK08
Language	English, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch , Spanish, Romanian, Estonian, Croatian, Slovenian, Serbian, Ukrainian, Portuguese
Indoor station	
Operation system	Embedded Linux operation system
RAM	32 MB
ROM	128 MB
Processor	Embedded processor
Indoor station	
Type	Colorful TFT screen
Operating method	Capacitive touch screen
Screen size	7-inch
Indoor station	
Video compression standard	/
Resolution	1024 × 600
Lens	/
Wide dynamic range (WDR)	/
FOV	/
Indoor station	
Audio input	1 Built-in omnidirectional microphone
Audio output	1 Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Audio compression standard	G.711 U, G.711 A
Audio compression bitrate	64 Kbps
Indoor station	
Notice capacity	200 captured pictures (with TF card)
Linked indoor extensions capacity	3
Indoor station	
Wired network	Two-wire network
Wireless network	2.4 GHz, IEEE802.11b, IEEE802.11g, IEEE802.11n
Network protocol	TCP/IP, SIP, RTSP
Indoor station	
RS-485	/
Alarm output	/


Alarm input	1
Power supply input	24VDC 2.5A
TF card	Max to 128 G, SD 2.0 or lower version
TAMPER	/
USB	/
Two-Wire	4, 1 for indoor station power in, 1 for indoor station power out, 1 for outdoor station power out, 1 for outdoor station out
DIP switch	2 decimal DIP switch and 1 binary DIP switch
Indoor station	
Button	3 Touch buttons (Answer, Unlock, Hang up)+1 Physical button (Reset)
Power supply	24 VDC, 2.5 A
Power consumption	≤ 6 W
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	10% to 90% (no-condensing)
Dimension (W × H × D)	190.2 mm × 138.2 mm × 20 mm (7.5" × 5.4" × 0.8")
Installation	Surface mounting
Application environment	Indoor
Protective level	/
Language	English, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch , Spanish, Romanian, Estonian, Croatian, Slovenian, Serbian, Ukrainian, Portuguese

▪ Available Model

DS-KIS708EY

▪ Dimension





Unit: mm [inch]

SCALE	1:1
-------	-----



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au